



PRODUCT SPECIFICATIONS

- Module Size:** **Width:** 24" / 60.96 cm / 609.6 mm
 Length: 12" / 30.48 cm / 304.8 mm
 Thickness: 1.25" Tall / 3.175 cm / 31.75 mm
- Module Weight:** 3.58 lbs. / 57.28 oz. / 1.62 kg. / 162 grams
 Per Square Foot: 1.79 lbs. / 28.64 oz. / 0.812 kg. / 812 grams
 Per Square Meter: 19.27 lbs. / 8.74 kg
- Material:** High-impact polypropylene co-polymer. UV Inhibitors added.
- Fire Rating:** UL 94HB (Underwriters Laboratory Yellow Card Number)
 This test signifies that this product does not flare up when exposed to an open flame and has a slow burn rate of 2" per minute for a 2" wide, 0.5 millimeter thickness test sample.
 ASTM 2859 (Flammability of Finished Texture Floor Covering Materials)
 – passed test
 * Testing report must be provided showing testing of actual product module
- Hot Wire Ignition Rating:** 3
- Melting Point:** 324 Fahrenheit / 162 Celsius
Operating Range: -10° F → 150°F / -23.33° C → 65.56° C
- Coefficient of Static Friction:** **Leather:** 0.57
ASTM C-1028 **Neoprene:** 0.48
- Support Structure:** Flooring module incorporates multi-directional structural support ribbing, allowing for distribution of weight and loads.
- Weight Loading:** 20,000 lbs sq/ft static load, solid sub-surface. Varies depending on sub-surface.
- Ground Surfaces:** EventDeck Ice is designed to be used with little surface preparation. It is recommended that the ice surface be dry cut prior to installation.



Shipping:	40" x 48" Pallet:	up to 816 sq/ft
	463L Pallet (83"L x 103"W x 96"H Max):	3,312 sq/ft
	20' Ocean Container:	8,160 sq/ft
	40' Ocean Container:	16,320 sq/ft
	Note: High cube container loads can be loaded with additional product.	
	48' Truck:	19,684 sq/ft
	53' Truck:	21,216 sq/ft

Functional Features:

- a) Individual modules interconnect to form larger flooring sections.
- b) Connection system allows for installation and disassembly *without* the need for connection or separation tools.
- c) Modules are designed to allow 90-degree rotation and still connect. Module can be connected in both directions and at any module connection point, allowing greater flexibility in floor design.
- d) Modules do not have any submerged channels into which debris or dirt can enter from the top surface, and are easy to clean and maintain.

Warranty: 3 Year warranty against manufacturer's defects.

The EventDeck Ice System consists of the UltraDeck* top layer and an additional molded bottom layer which prevents ice rutting (from underside pattern), offers additional traction, seals off EDU cable channels, and provides additional insulation benefits.

**Signature System Group, LLC's UltraDeck products are not in any way affiliated, endorsed, or sponsored by Menard, Inc. or any of Menard, Inc.'s affiliates or subsidiaries.*

