



PRODUCT SPECIFICATIONS

Module Size:	Width: 24" / 60.96 cm / 609.6 mm Length: 12" / 30.48 cm / 304.8 mm Thickness: 1.25" Tall / 3.175 cm / 31.75 mm
Module Weight:	3.58 lbs. / 57.28 oz. / 1.62 kg. / 162 grams Per Square Foot: 1.79 lbs. / 28.64 oz. / 0.812 kg. / 812 grams Per Square Meter: 19.27 lbs. / 8.74 kg
Material:	High-impact polypropylene co-polymer. UV Inhibitors added.
Fire Rating:	UL 94HB (Underwriters Laboratory Yellow Card Number) This test signifies that this product does not flare up when exposed to an open flame and has a slow burn rate of 2" per minute for a 2" wide, 0.5 millimeter thickness test sample. ASTM 2859 (Flammability of Finished Texture Floor Covering Materials) – passed test * Testing report must be provided showing testing of actual product module
Hot Wire Ignition Rating:	3
Melting Point:	324 Fahrenheit / 162 Celsius Operating Range: -10° F → 150°F / -23.33° C → 65.56° C
Coefficient of Static Friction: ASTM C-1028	Leather: 0.57 Neoprene: 0.48
Support Structure:	Flooring module incorporates multi-directional structural support ribbing, allowing for distribution of weight and loads.
Weight Loading:	20,000 lbs sq/ft static load, solid sub-surface. Varies depending on sub-surface.
Ground Surfaces:	EventDeck Ice is designed to be used with little surface preparation. It is recommended that the ice surface be dry cut prior to installation.
Shipping:	40" x 48" Pallet: up to 816 sq/ft 463L Pallet (83"L x 103"W x 96"H Max): 3,312 sq/ft 20' Ocean Container: 8,160 sq/ft 40' Ocean Container: 16,320 sq/ft Note: High cube container loads can be loaded with additional product. 48' Truck: 19,684 sq/ft 53' Truck: 21,216 sq/ft

**Functional
Features:**

- a) Individual modules interconnect to form larger flooring sections.
- b) Connection system allows for installation and disassembly *without* the need for connection or separation tools.
- c) Modules are designed to allow 90-degree rotation and still connect. Module can be connected in both directions and at any module connection point, allowing greater flexibility in floor design.
- d) Modules do not have any submerged channels into which debris or dirt can enter from the top surface, and are easy to clean and maintain.

Warranty: 3 Year warranty against manufacturer's defects.

The EventDeck Ice System consists of the UltraDeck top layer and an additional molded bottom layer which prevents ice rutting (from underside pattern), offers additional traction, seals off EDU cable channels, and provides additional insulation benefits.



Signature Fencing & Flooring Systems, LLC
50 East 42nd Street • Suite 501
New York, NY 10017
Toll Free: 800-569-2751 • 212-953-1116 • Fax: 212-953-1117
Flooring: www.eventdeck.com • *Fencing:* www.signaturefencing.com