



PRODUCT SPECIFICATIONS

Module Size: 3.00 sq/ft in Hexagonal configuration – 26” wide at widest point
Height: 1.9”

Module Weight: 6 lbs. / 96 oz. / 2.72 kg. / 2772 grams
Per Square Foot: 2 lbs. / 32 oz. / 0.91 kg. / 907 grams
Per Square Meter: 21.5 lbs. / 9.75 kg.

Material: High-Density Polyethylene. UV Inhibitors added.

Fire Rating: UL 94HB (Underwriters Laboratory Yellow Card Number)
This test signifies that this product does not flare up when exposed to an open flame and has a slow burn rate of 2” per minute for a 2” wide, 0.5 millimeter thickness test sample. EventDeck meets applicable standards for temporary floor covers.
ASTM 2859 (Flammability of Finished Texture Floor Covering Materials)
– passed test
* Testing reports available for fire ratings

Hot Wire Ignition Rating: 3

Melting Point: 324 Fahrenheit / 162 Celsius

Support Structure: Flooring module incorporates multi-directional, concentric, structural support ribbing, allowing for distribution of weight and loads. Reinforcement ribbing width is 0.14” (over 1/8”).

Weight Loading: 30,000 lbs. sq/ft static load, solid sub-surface
Suitable for light and heavy pedestrian and vehicle use on multiple ground surfaces.

Functional Features:

- Tiles are designed to nest into each other, locking each tile down and together using a unique over-and-under connection system.
- Individual modules interconnect to form larger flooring sections. Sections can be added to any side of the HexaDeck module.
- Connection system allows for assembly and disassembly *without* the need for separation tools. There are no loose parts – each tile is a complete piece and required no additional pieces to function alone or in conjunction with adjacent sections.



Signature Systems Group, LLC
50 East 42nd Street • 14th Floor
New York, NY 10017

Toll Free: 800-569-2751 • 212-953-1116 • Fax: 212-953-1117
Flooring: www.eventdeck.com • Fencing: www.signaturefencing.com

d) Tile features diamond-plate finish for added slip resistance and drainage holes to prevent water build-up.

Grass Protection

Features:

- a) Tiles feature an integrated moisture canopy that allows for moisture retention.
- b) HexaDeck incorporates drainage holes that provide ventilation, air and small amounts of light to grass below.
- c) Underside is specially designed to protect grass by distributing weight across multiple support ribs. No sharp, unsupported edges exist to damage grass or synthetic turf.
- d) Module canopy is raised 1.85 inches off of ground surface.

Warranty:

3-year warranty against manufacturer's defects.



Signature Systems Group, LLC
50 East 42nd Street • 14th Floor
New York, NY 10017

Toll Free: 800-569-2751 • 212-953-1116 • Fax: 212-953-1117

Flooring: www.eventdeck.com • *Fencing:* www.signaturefencing.com