



PRODUCT SPECIFICATIONS

Description:	Heavy duty, roll-out mats and interlocking rubber tiles for cushioned support.		
Colors:	Standard Colors: Solid Black, Blue Flec, Gray Flec, Yellow Flec, Green Flec, Red Flec, Blue/Gray Flec. Custom colors available.		
Material:	Recycled rubber and polymer binding agents.		
Size:	Interlocking Tiles: 28.5" x 28.5" Roll-Out Mats: 4' x 25', 4' x 50', 4' x 75'.		
Thickness:	Interlocking Tiles: 0.375". Roll-Out Mats: 0.25", 0.375".		
Diameter – Roll-Out Mats:	<u>4' x 25'</u>	<u>4' x 50'</u>	<u>4' x 75'</u>
0.25":	10.5"	14.5"	18"
0.375":	13"	18"	21"
Weight:	Interlocking Tiles: 11.28 lbs. Roll-Out Mats: 0.25": 20.8 oz. per sq/ft 0.375": 27.6 oz. per sq/ft		
Chemical Behavior:	Resistant to water, numerous diluted acids and alkaline solutions. Chemically neutral. UV Resistant.		
Density: ASTM D 3676	60 lbs./ft ³		
Elongation:	< 145%		
Shearing Strength:	< 0.60 (N/mm ²)		
Tensile Strength:	< 1.80 (N/mm ²)		
Temperature Stability:	-30°C up + 80°C in resting conditions		
Flammability:	Passes Federal Flammability Standard Doc FF 1-70 CPSC.		
Friction Coefficient:	0.96 dry		

Compression &

Recovery:

ASTM D 575

After 48 hours 99.4%

After 72 hours 99.7%

After 96 hours 99.7%

ACCESSORIES

Polyurethane

Adhesive:

1. One-component polyurethane-based trowel-grade, structural adhesive.
2. Suitable for indoor and outdoor applications.
3. Covers 60 sq/ft per gallon.
4. Provides excellent initial grab and outstanding bond strength.
5. No Water – Freeze/thaw stable.
6. Meets flame spread requirements: NFPA – Class A, and UBC – Class I.
7. VOC compliant, extremely low odor.
8. Can be used on concrete, plywood, particle/chip board, cement and gypsum underlayment, radiant heat flooring, and asphalt.
9. Application temperature: above 40°F

Double-Sided

Carpet Tape:

1. 5” W x 60’ L
2. Very aggressive!!!

Edging:

1. 12 ft long.
2. Usable with 0.375” mat thickness only.
3. Use carpet tape to secure in position.

Warranty:

2-year warranty against manufacturer’s defects.



Signature Fencing & Flooring Systems, LLC

50 East 42nd Street • Suite 501

New York, NY 10017

Toll Free: 800-569-2751 • 212-953-1116 • Fax: 212-953-1117

Flooring: www.eventdeck.com • Fencing: www.signaturefencing.com